=Parker		
Home		
Products		
<u>Support</u>		
Industries		
<u>Services</u>		
Solutions		
<u>Where to Buy</u>		

Home / Products / Filters, Collectors, Separa... / Replacement Engine and Mobi... / Hydraulic Filter Elements / Replacement Elements - High... / 1111300028-01

Replacement Elements - High Pressure In-Line Filter 70/70 Eco Series

Part #: 1111300028-01



High pressure inline hydraulic oil filter series is a proven filter concept, up to 500l/min and pressures up to 420 bar.

View Series Page ☷

View Catalog(s) 🗹

Share / Email 🔿

Print 🖶

Ð

Technical Specifications

Division:	Hydraulic and Industrial Process Filtration EMEA	Options:	None Drilling machines	
For Use With:	70 series length 3			
Filter Element Type:	Filter Element Type: 60M Wiremesh		Dumpers Hydraulic power units	
Brand:	Parker	Application:	Mobile cranes Reach stackers Container handling equipment Cranes Excavators Crushing machines Propulsion systems Deck machinery Wind turbines Hydropower Servo controls	
Technology:	Filtration			
Micron Rating:	60 µm			
Seal Material:	Fluoroelastomer			
Product Type:	Hydraulic Oil Filter Replacement Elements			
Product Series:	70/70 Eco Series			
Length:	328 mm			
End Cap Material:	Tin plated steel			
	Mining			
Industry:	Material handling Construction	For Fluid Type:	Suitable for use with mineral and vegetable oils, and some synthetic oils.	
	Marine	Operating Pressure:	420 bar (350 bar Length 4) Maximum.	
	Power Generation Industrial Machinery Injection Moulding	Operating Temperature:	-20°C to +120°C.	
A Safety Warning				

Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.

Typical Applications

- Mobile working hydraulics
- Mobile drive system
- Injection moulding
- Servo controls
- Die casting
- Machine tools
- Industrial power units

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS