

# Replacement Elements - High Pressure In-Line Filter 70/70 Eco Series

Part #: 1111713053-01



High pressure inline hydraulic oil filter series is a proven filter concept, up to 500l/min and pressures up to 420 bar.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Qty:

1



Find a Distributor

Division Contact

Parker Sales

Tachbrook Park  
Tachbrook Park  
Warwick  
United Kingdom  
CV34 6TU

Phone: +44

## Technical Specifications

Division:	Hydraulic and Industrial Process Filtration EMEA		
For Use With:	70 series length 3		
Brand:	Parker		
Filter Element Type:	05Q Microglass		
Technology:	Filtration		
Micron Rating:	5 µm		
Product Type:	Hydraulic Oil Filter Replacement Elements	Application:	Drilling machines Dumpers Hydraulic power units Mobile cranes Reach stackers Container handling equipment Cranes Excavators Crushing machines Propulsion systems Deck machinery Wind turbines Hydropower Servo controls
Seal Material:	Nitrile		
Product Series:	70/70 Eco Series		
Length:	328 mm		
End Cap Material:	Plastic	Options:	Epoxy glued end caps
	Mining	For Fluid Type:	Suitable for use with mineral and vegetable oils, and some synthetic oils.
	Material handling	Operating Pressure:	420 bar (350 bar Length 4) Maximum.
	Construction	Operating Temperature:	-40°C to +100°C.
	Marine		
	Power Generation		
	Industrial Machinery		
	Injection Moulding		

 Safety Warning

## Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.

- Typical Applications
- Mobile working hydraulics
  - Mobile drive system
  - Injection moulding
  - Servo controls
  - Die casting
  - Machine tools
  - Industrial power units

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

+

Related Documents

+



Parker Sales Company UK

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)

[+44 \(0\)1926 317878](tel:+441926317878)

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

