

Replacement Elements - High Pressure In-Line Filter 70/70 Eco Series

Part #: 1111714051-01



High pressure inline hydraulic oil filter series is a proven filter concept, up to 500l/min and pressures up to 420 bar.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Qty:



Find a Distributor

Division Contact

Parker Sales

Tachbrook Park
Tachbrook Park
Warwick
United Kingdom
CV34 6TU

Phone: +44

Technical Specifications

For Use With:	70 series length 1
Division:	Hydraulic and Industrial Process Filtration EMEA
Filter Element Type:	02Q Microglass
Brand:	Parker
Technology:	Filtration
Micron Rating:	2 µm
Seal Material:	EPDM
Product Type:	Hydraulic Oil Filter Replacement Elements
Product Series:	70/70 Eco Series
Length:	115 mm
End Cap Material:	Plastic
Industry:	Mining Material handling Construction Marine Power Generation Industrial Machinery Injection Moulding

Options:	None Drilling machines Dumpers Hydraulic power units Mobile cranes Reach stackers Container handling equipment
Application:	Cranes Excavators Crushing machines Propulsion systems Deck machinery Wind turbines Hydropower Servo controls
For Fluid Type:	Suitable for use with mineral and vegetable oils, and some synthetic oils.
Operating Pressure:	420 bar (350 bar Length 4) Maximum.
Operating Temperature:	-

Safety Warning

Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.

Typical Applications

- Mobile working hydraulics
- Mobile drive system
- Injection moulding
- Servo controls
- Die casting
- Machine tools
- Industrial power units

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

