|   | -Parker      |
|---|--------------|
|   | Home         |
|   | Products     |
|   | Support      |
|   | Industries   |
|   | Services     |
|   | Solutions    |
|   | Where to Buy |
| - |              |

Home / Products / Filters, Collecto... / Replacement Filte... / Lubrication Oil F... / Replacement Eleme... / 1181301240-01

## 

For Use With: Filter Element Type: Micron Rating: Length: A Safety Warning GS2 035W Wiremesh 35 μm 149 mm Diameter: Seal Material: Options: 72 mm No seal Standard

## **Item Information**

The high quality replacement elements of the GS filter series are available in a wide variety of sizes and with several filter materials and micron ratings.

These replacement elements ensure the quality of filtration Parker is known for.

Fluid passes through the elements in an inside-to-outside direction, collecting particles inside the filter cartridge. This eliminates re-injection of contaminant during element change. Clean fluid then returns to the reservoir.

The GS series filters are available with Magnetic pre-filtration. The magnet column removes ferrous particles, even during times of bypass, and extends the life of the filter element.

Using genuine Parker replacement elements guarantees Parker's quality of filtration. Using after market filters with unknown media quality may save initial cost, but can increase overall costs by requiring more element change outs and potentially causing system downtime. Protect your investment by always buying genuine Parker replacement elements.

## CAD Drawings + Files

Qty:

Tł au

or

w

Find a Distribu

**Division Conta** 

Parker Sales C

Tachbrook Par

+44 ((

Warwick United Kingdor

CV34 6TU Phone:



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS. SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS

 $\bigcirc$