

High Pressure Inline Filter 12S Series

[Solutions](#)
Part #: 12SMP105QHV4L35N811
[Where to Buy](#)


Parker's 12S High Pressure Stainless Steel Inline Filters are ideal for heavy duty applications in aggressive environments. Allowable operating pressure of 20,000 psi/1,380 bar and capable of flows up to 25 GPM/95 LPM depending on viscosity.

[View Series Page](#) [Share / Email](#) [Print](#)

Qty:


[Find a Distributor](#)
[Division Contact](#)

Parker Sales Co

Tachbrook Park
Tachbrook Park
Warwick
United Kingdom
CV34 6TU

Phone: +44

Technical Specifications

Options:	No bypass	Bypass Valve Pressure Rating:	N/A
Seal Material:	Fluorocarbon	Port Type:	1/2 NPTF
Bypass Valve Pressure Rating:	N/A	Indicator Type:	Electrical/Visual (DIN 43650 style connection)
Indicator Type:	Electrical/Visual (DIN 43650 style connection)	Indicator Pressure Setting:	N/A
Port Connection Type:	1/2 NPTF	Options:	No bypass
Filter Element:	5 micron microglass	Housing Material:	Stainless Steel 316L
Flow Rate:	10 gpm (37.8 lpm)	For Fluid Type:	Mineral, Petroleum and Polyalphaolefin (PAO) based fluids
Mounting Style:	Inline	Maximum Operating Temperature:	275 F (135 C)
Pressure Rating:	10000 psi (689 bar)	Weight:	14 lbs (6.35 kg)
Flow Rate:	10 gpm (37.8 lpm)	Compatible Element:	403398
Filter Element Type:	5 micron microglass, Cartridge	Product Type:	Hydraulic Filter
Seal Material:	Fluorocarbon		

[Safety Warning](#)

Item Information

The 12S Series is designed to meet the growing demand for high-pressure systems. Stainless Steel construction engineered to handle flow rates of up to 25 GPM/95 LPM at 20,000 psi/1,380 bar working pressure, Parker's 12S Filter Series designed to perform in harsh environments.

High strength Microglass elements withstand differential pressures up to 2,000 psid/138 bar to ensure system reliability and protect critical equipment from contamination.

Product Features:

- 316L stainless steel construction
- Diverse porting options adapt to your system
- Light weight design for ease of changeouts
- High strength multi-layer Microglass filter elements
- 100% pressure tested
- Maximum pressure 20,000 psi/1,380 bar. Maximum flow 25 gpm/95 lpm

Typical Applications:





High Pressure Test Stands

[Home](#)

CAD Drawings + Files



[Support](#)

Related Documents



[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

Parker Sales Company UK

psc.uk.webform@support.parker.com

+44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

