

Medium Pressure In-Line Filter - 130 Series

Part #: 130M102QBM3KG242S03



The 130 series is a range of high flow return filters for industrial use on hydraulic or lubrication systems. Flow up to 1400 l/min and pressure up to 30 bar in single units.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Indicator Type:	Visual	Options:	1 Single Unit
Filter Element Type:	02QE Ecoglass	Seal Material:	Nitrile
Product Style:	Single unit	Micron Rating:	2 µm
Flow Rate:	0 - 350 l/min	Connection Type:	G1½
Bypass Valve Pressure Rating:	No by pass		

[Safety Warning](#)

Item Information

Items marked with an asterisk * in the drop-down menus are standard choices.

The 130 series is a range of high flow return filters for industrial use on hydraulic or lubrication systems. Flow up to 1400 l/min and pressure up to 30 bar in single units. Ability to bank multiple filters together enables continuous filtration during element changes. Coreless Ecoglass III elements.

- Typical applications:
- Paper production plants
 - Steel mills
 - Aluminium mills
 - Industrial power packs
 - Lubrication systems
 - Power generation

CAD Drawings + Files

Qty:



Find a Distributor

Division Contact

Parker Sales C
Tachbrook Park
Tachbrook Park
Warwick
United Kingdom
CV34 6TU

Phone: +44

Related Products

Medium Pressure
Inline Hydraulic Oil
Filter – iProtect® GMF
Series



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

