

# Medium Pressure In-Line Filter - 130 Series

Part #: 130M205QEBM3KG241



The 130 series is a range of high flow return filters for industrial use on hydraulic or lubrication systems. Flow up to 1400 l/min and pressure up to 30 bar in single units.

[View Series Page](#)
[Share / Email](#)
[Print](#)

## Technical Specifications

Flow Rate:	0 to 500 l/min	Micron Rating:	5 µm
Product Style:	Single unit	Pressure Rating:	70 bar
Options:	1 Single Unit	Flow Rate:	900 L/min
Connection Type:	G1½	Housing Material:	Aluminium
Filter Element Type:	05QE Ecoglass	Operating Temperature:	-40 / 100 °C
Bypass Valve Pressure Rating:	3,5 * bar	Indicator Type:	Visual
Mounting Type:	Inline	Seal Material:	Nitrile

 [Safety Warning](#)

## Item Information

Items marked with an asterisk \* in the drop-down menus are standard choices.

The 130 series is a range of high flow return filters for industrial use on hydraulic or lubrication systems. Flow up to 1400 l/min and pressure up to 30 bar in single units. Ability to bank multiple filters together enables continuous filtration during element changes. Coreless Ecoglass III elements.

- Typical applications:
- Paper production plants
  - Steel mills
  - Aluminium mills
  - Industrial power packs
  - Lubrication systems
  - Power generation

Qty:



Find a Distributor

Division Contact

Parker Sales Co  
Tachbrook Park  
Tachbrook Park  
Warwick  
United Kingdom  
CV34 6TU

Phone: +44 (0)



Medium Pressure  
Inline Hydraulic Oil  
Filter – iProtect® GMF  
Series



Parker Sales Company UK  
[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



