



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Lubrication Oil F...](#) / [Medium Pressure I...](#) / 130M302QEV3KR401

Medium Pressure In-Line Filter - 130 Series

Part #: 130M302QEV3KR401



The 130 series is a range of high flow return filters for industrial use on hydraulic or lubrication systems. Flow up to 1400 l/min and pressure up to 30 bar in single units.

[View Series Page](#) ☰ [Share / Email](#) ↗ [Print](#) 🖨

Technical Specifications -

Flow Rate:	0 to 850 l/min	Mounting Type:	Inline
Connection Type:	2½" SAE-3000M	Pressure Rating:	70 bar
Filter Element Type:	02QE Ecoglass	Flow Rate:	1150 L/min
Product Style:	Single unit	Housing Material:	Aluminium
Options:	1 Single Unit	Operating Temperature:	-20 / 120 °C
Micron Rating:	2 µm	Indicator Type:	Visual
Bypass Valve Pressure Rating:	3,5 * bar	Seal Material:	Fluorelastomer

[Safety Warning](#)

Item Information +

CAD Drawings + Files +

Related Documents +



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

