



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Lubrication Oil F...](#) / [Medium Pressure I...](#) / 130M305QEBM3KG241

Medium Pressure In-Line Filter - 130 Series

Part #: 130M305QEBM3KG241



The 130 series is a range of high flow return filters for industrial use on hydraulic or lubrication systems. Flow up to 1400 l/min and pressure up to 30 bar in single units.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Product Style:	Single unit	Mounting Type:	Inline
Options:	1 Single Unit	Pressure Rating:	70 bar
Flow Rate:	0 to 600 l/min	Flow Rate:	1150 L/min
Connection Type:	G1½	Housing Material:	Aluminium
Filter Element Type:	05QE Ecoglass	Operating Temperature:	-40 / 100 °C
Bypass Valve Pressure Rating:	3,5 * bar	Indicator Type:	Visual
Micron Rating:	5 µm	Seal Material:	Nitrile

[Safety Warning](#)

Item Information

CAD Drawings + Files

Related Documents



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)
AOG (Aircraft on Ground)
[1-949-851-4357](tel:1-949-851-4357)

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

