



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Lubrication Oil F...](#) / [Medium Pressure I...](#) / 130M305QEBM3KR401

Medium Pressure In-Line Filter - 130 Series

Part #: 130M305QEBM3KR401



The 130 series is a range of high flow return filters for industrial use on hydraulic or lubrication systems. Flow up to 1400 l/min and pressure up to 30 bar in single units.

[View Series Page](#) ≡ [Share / Email](#) ↗ [Print](#) 🖨

Technical Specifications -

Connection Type:	2½" SAE-3000M	Micron Rating:	5 µm
Flow Rate:	0 to 900 l/min	Pressure Rating:	70 bar
Product Style:	Single unit	Flow Rate:	1150 L/min
Options:	1 Single Unit	Housing Material:	Aluminium
Filter Element Type:	05QE Ecoglass	Operating Temperature:	-40 / 100 °C
Bypass Valve Pressure Rating:	3,5 * bar	Indicator Type:	Visual
Mounting Type:	Inline	Seal Material:	Nitrile

[Safety Warning](#)

Item Information +

CAD Drawings + Files +

Related Documents +



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:0080027275374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

