



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Lubrication Oil F...](#) / [Medium Pressure I...](#) / 130S310QEBM3KD10041

Medium Pressure In-Line Filter - 130 Series

Part #: 130S310QEBM3KD10041



The 130 series is a range of high flow return filters for industrial use on hydraulic or lubrication systems. Flow up to 1400 l/min and pressure up to 30 bar in single units.

[View Series Page](#) ≡ [Share / Email](#) ↗ [Print](#) 🖨

Technical Specifications -

Flow Rate:	0 to 1200 l/min	Micron Rating:	10 µm
Options:	T-system 2+2 Units	Pressure Rating:	16 bar
Connection Type:	DN100/PN16	Flow Rate:	1800 L/min
Filter Element Type:	10QE Ecoglass	Housing Material:	Aluminium
Product Style:	System with ball valve	Operating Temperature:	-40 / 100 °C
Bypass Valve Pressure Rating:	3,5 * bar	Indicator Type:	Visual
Mounting Type:	Inline	Seal Material:	Nitrile

[Safety Warning](#)

Item Information +

CAD Drawings + Files +

Related Documents +



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2023

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

