



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Fil... / 15P105QBM3KG121

High Pressure Filters - 15P/30P Series

Part #: 15P105QBM3KG121



High pressure hydraulic filters for flow rates up to 200 l/min, with a maximum flow rate of 207 bar.

[View Series Page](#) ≡

[View Catalog\(s\)](#) ↗

[Share / Email](#) ↗

[Print](#) 🖨

Technical Specifications

Length:	Length 1		
Port Size:	G¾		
Filter Element Type:	Q005 microglass		
Flow Rate:	0 to 40 l/min	Application:	<ul style="list-style-type: none"> • Saw mills • Aircraft ground support equipment • Asphalt pavers • Hydraulic fan drives • Power steering circuits • Domestic refuse vehicles • Cement trucks • Servo control protection • Logging equipment
Filter Type:	15P		
Division:	Hydraulic and Industrial Process Filtration		
	EMEA		
Brand:	Parker	Pressure Rating:	2.5 bar
Technology:	Filtration	Seal Material:	Nitrile
Product Type:	Hydraulic Filter	Bypass Valve Pressure Rating:	3.5 bar
Filter Type:	High Pressure Filter	Options:	None
Product Series:	15P/30P Series		

[Safety Warning](#)

Item Information



CAD Drawings + Files



Related Documents





Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

