

**Home** 

Products ~

Help & Support

**Industries** 

Where To Buy

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / 15P110QBM2KS121

# High Pressure Inline/Duplex Filter 15P/30P/30PD Series

# Part #: 15P110QBM2KS121







The Parker 15P/30P Series is a high pressure all aluminum filter assembly that comes in a variety of options. The 15P/30P Series has a rated fatigue pressure of up to 2,000psi and flow rate up to 45gpm.

View Series Page **Ξ** 

View Catalog(s)

Share / Email 🗪

Print =

# **Technical Specifications**

Mounting Style: Seal Material: nitrile

Indicator Type: visual automatic reset

inline

Micron Rating: 10Q microglass Options: none

Flow Rate: 15 GPM (56 LPM)

Port Connection SAE-12 ports Type:

3000 psi (206.9 bar) Pressure Rating: Flow Rate: 15 GPM ( 56 LPM) 10Q microglass Micron Rating:

nitrile Seal Material:

Bypass Valve 50 psid (3.5 bar) Pressure Rating: Port Type: SAE-12 ports Indicator Type:

Setting: Options:

Housing

Indicator Pressure

bowl - impacted aluminum (6061-T6, black powderpainted Material: exterior); head - extruded aluminum (anodized 6061-T6 Filter Element

cartridge Type:

Suitable for use with mineral and vegetable oils, and some synthetic oils. For other fluids, please email Technical For Fluid Type: Support at HFF.techsupport@support.parker.com or call

800-253-1258

50 PSI (3.5 bar)

Maximum Operating 225 F (107 C)

Temperature: Weight: 3.5 lb (1.6 kg) Compatible 932612Q Element: Hydraulic Filter Product Style:

Product Type: Hydraulic Filter

▲ Safety Warning

### Item Information



# **CAD Drawings + Files**



## **Related Documents**





#### Americas

USA, Canada, Mexico

<u>cparker@support.parker.com</u> 1-800-272-7537

Europe

00800 27 27 5374

AOG (Aircraft on Ground)

1-949-851-4357

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us:

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS