



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure Fil...](#) / 15P110QBM3KG121

High Pressure Filters - 15P/30P Series

Part #: 15P110QBM3KG121



High pressure hydraulic filters for flow rates up to 200 l/min, with a maximum flow rate of 207 bar.

[View Series Page](#) ≡

[View Catalog\(s\)](#) ↗

[Share / Email](#) ↗

[Print](#) 🖨

Technical Specifications

Length:	Length 1	
Flow Rate:	0 to 50 l/min	
Port Size:	G¾	
Filter Type:	15P	Application:
Filter Element Type:	Q010 microglass	• Saw mills
Division:	Hydraulic and Industrial Process Filtration	• Aircraft ground support equipment
Brand:	EMEA	• Asphalt pavers
Technology:	Parker	• Hydraulic fan drives
Product Type:	Filtration	• Power steering circuits
Filter Type:	Hydraulic Filter	• Domestic refuse vehicles
Product Series:	High Pressure Filter	• Cement trucks
	15P/30P Series	• Servo control protection
		• Logging equipment
		Pressure Rating:
		2.5 bar
		Seal Material:
		Nitrile
		Bypass Valve Pressure
		Rating:
		3.5 bar
		Options:
		None

[Safety Warning](#)

Item Information



CAD Drawings + Files



Related Documents





Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

