



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure Fil...](#) / [15P110QBT1KG121](#)

High Pressure Filters - 15P/30P Series

Part #: 15P110QBT1KG121



High pressure hydraulic filters for flow rates up to 200 l/min, with a maximum flow rate of 207 bar.

[View Series Page](#) ≡

[View Catalog\(s\)](#) ↗

[Share / Email](#) ↗

[Print](#) 🖨

Technical Specifications

Length:	Length 1		
Flow Rate:	0 to 50 l/min		
Port Size:	G¾		
Filter Type:	15P	Application:	<ul style="list-style-type: none">• Saw mills• Aircraft ground support equipment• Asphalt pavers• Hydraulic fan drives• Power steering circuits• Domestic refuse vehicles• Cement trucks• Servo control protection• Logging equipment
Filter Element Type:	Q010 microglass		
Division:	Hydraulic and Industrial Process Filtration		
Brand:	EMEA		
Technology:	Parker	Pressure Rating:	2.5 bar
Product Type:	Filtration	Seal Material:	Nitrile
Filter Type:	Hydraulic Filter	Bypass Valve Pressure Rating:	3.5 bar
Product Series:	High Pressure Filter	Options:	None
	15P/30P Series		

[Safety Warning](#)

Item Information



CAD Drawings + Files



Related Documents





Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)
AOG (Aircraft on Ground)
[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

