≡ —⊋arke	r
<u>Home</u>	
<u>Products</u> ∽	
Help & Support	
Industries	
Where To Buy	
Home / Products / F	

# High Pressure Filters - 15P/30P Series

### Part #: 15P205QBT1KG121



High pressure hydraulic filters for flow rates up to 200 l/min, with a maxumum flow rate of 207 bar.

View Series Page ☷	View Catalog(s) 🗹
Share / Email 🔿	Print 🖶

## **Technical Specifications**

Flow Rate:	0 to 70 l/min		• Saw mills
Length:	Length 2		<ul> <li>Aircraft ground support equipment</li> <li>Asphalt pavers</li> </ul>
Port Size:	G34	Application:	<ul> <li>Hydraulic fan drives</li> <li>Power steering circuits</li> </ul>
Filter Element Type:	Q005 microglass		
Filter Type:	15P		Domestic refuse vehicles
Division:	Hydraulic and Industrial Process Filtration EMEA	Pressure Rating:	Cement trucks     Servo control protection     Logging equipment     2.5 bar
Brand:	Parker		
Technology:	Filtration	Seal Material:	Nitrile
Product Type:	Hydraulic Filter	Bypass Valve Pressure	
Filter Type:	High Pressure Filter	Rating:	3.5 bar
Product Series:	15P/30P Series	Options:	None
▲ Safety Warning			

#### **Item Information**

## **CAD Drawings + Files**

#### **Related Documents**

╇



Americas

USA, Canada, Mexico

cparker@support.parker.com 1-800-272-7537

Europe

00800 27 27 5374 AOG (Aircraft on Ground)

<u>1-949-851-4357</u>

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

 ENGINEERING YOUR SUCCESS.

 SITE MAP
 SAFETY

 PRIVACY POLICIES
 TERMS AND CONDITIONS