

Home

Products ~

Help & Support

Industries

Where To Buy

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / 15P210QBM2KS121

High Pressure Inline/Duplex Filter 15P/30P/30PD Series

Part #: 15P210QBM2KS121







The Parker 15P/30P Series is a high pressure all aluminum filter assembly that comes in a variety of options. The 15P/30P Series has a rated fatigue pressure of up to 2,000psi and flow rate up to 45gpm.

View Series Page **Ξ**

View Catalog(s)

Share / Email 🗪

Print =

Technical Specifications

Mounting Style: inline Seal Material: nitrile

Indicator Type: visual automatic reset Micron Rating: 10Q microglass Options:

Flow Rate: 20 GPM (75 LPM) Port Connection

SAE-12 ports Type:

Bypass Valve 50 psid (3.5 bar) Pressure Rating:

Pressure Rating: 3000 psi (206.9 bar) Flow Rate: 20 GPM (75 LPM) Micron Rating: 10Q microglass Seal Material: nitrile

Port Type: SAE-12 ports Indicator Type: visual automatic reset Indicator

Pressure 50 PSI (3.5 bar)

Setting:

Options: Housing

bowl - impacted aluminum (6061-T6, black powderpainted Material: exterior); head - extruded aluminum (anodized 6061-T6 Filter Element

Type:

cartridge

Suitable for use with mineral and vegetable oils, and some synthetic oils. For other fluids, please email Technical For Fluid Type: Support at HFF.techsupport@support.parker.com or call

800-253-1258 225 F (107 C)

Maximum Operating

Temperature: Weight:

4.6 lb (2.1 kg) Compatible 932618Q Element:

Hydraulic Filter Product Style: Product Type: Hydraulic Filter

▲ Safety Warning

Item Information



CAD Drawings + Files



Related Documents





Americas

USA, Canada, Mexico

<u>cparker@support.parker.com</u> 1-800-272-7537

Europe

00800 27 27 5374

AOG (Aircraft on Ground)

1-949-851-4357

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us:

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS