



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In-...](#) / 18P105QBT1MG121

High Pressure In-Line Filter - 18/28/38P Series

Part #: 18P105QBT1MG121



18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

[View Series Page](#) ☰ [Share / Email](#) ↗ [Print](#) 🖨

Technical Specifications -

| | | | |
|-------------------------------|----------------|-----------------------------|--------------------------|
| Flow Rate: | 0-120 l/min | Indicator Type: | Electrical NO/NC |
| Length: | Length 1 | Indicator Pressure Setting: | 5.0 bar |
| Filter Element Type: | 05Q Microglass | Connection Type: | Thread G $\frac{3}{4}$ " |
| Micron Rating: | 5 μ m | Operating Temperature: | -40/+100°C |
| Seal Material: | Nitrile | Options: | Standard, incl. Bypass |
| Bypass Valve Pressure Rating: | 7.0 bar | | |

[Safety Warning](#)

Item Information +

CAD Drawings + Files +

Related Documents +



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

