



- Home
- Products ▾
- Help & Support
- Industries
- Where To Buy

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure In-... / 18P105QHVT1MG122

# High Pressure In-Line Filter - 18/28/38P Series

Part #: 18P105QHVT1MG122



18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Flow Rate:	0-90 l/min	Indicator Type:	Electrical NO/NC
Length:	Length 1	Indicator Pressure Setting:	5.0 bar
Filter Element Type:	05QH High Strength Microglass	Connection Type:	Thread G <sup>3</sup> / <sub>4</sub> "
Micron Rating:	5 µm	Operating Temperature:	-20/+120°C
Seal Material:	Fluorelastomer	Options:	No Bypass
Bypass Valve Pressure Rating:	7.0 bar		

[Safety Warning](#)

## Item Information

## CAD Drawings + Files

## Related Documents



Americas  
USA, Canada, Mexico

[cparker@support.parker.com](mailto:cparker@support.parker.com)  
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)  
AOG (Aircraft on Ground)  
[1-949-851-4357](tel:1-949-851-4357)

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

