



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In...](#) / 18P110QBM3KS121

# High Pressure In-Line Filter - 18/28/38P Series

Part #: 18P110QBM3KS121



18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

[View Series Page](#) ☰ [Share / Email](#) ↗ [Print](#) 🖨

## Technical Specifications -

Flow Rate:	0-90 l/min	Indicator Type:	Visual
Length:	Length 1	Indicator Pressure Setting:	2.5 bar
Filter Element Type:	10Q Microglass	Connection Type:	Thread SAE 12
Micron Rating:	10 µm	Operating Temperature:	-40/+100°C
Seal Material:	Nitrile	Options:	Standard, incl. Bypass
Bypass Valve Pressure Rating:	3.5 bar		

[Safety Warning](#)

## Item Information +

## CAD Drawings + Files +

## Related Documents +



**Americas**

USA, Canada, Mexico

[cparker@support.parker.com](mailto:cparker@support.parker.com)  
[1-800-272-7537](tel:1-800-272-7537)

**Europe**

[00800 27 27 5374](tel:0080027275374)

**AOG (Aircraft on Ground)**

[1-949-851-4357](tel:1-949-851-4357)

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

---

© PARKER HANNIFIN CORP 2024

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

