



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In-...](#) / 18P110QBPMG121

High Pressure In-Line Filter - 18/28/38P Series

Part #: 18P110QBPMG121



18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

[View Series Page](#) ☰ [Share / Email](#) ↗ [Print](#) 🖨

Technical Specifications -

Flow Rate:	0-140 l/min	Indicator Type:	Plugged with steel plug
Length:	Length 1	Indicator Pressure Setting:	No indicator
Filter Element Type:	10Q Microglass	Connection Type:	Thread G $\frac{3}{4}$ "
Micron Rating:	10 μ m	Operating Temperature:	-40/+100°C
Seal Material:	Nitrile	Options:	Standard, incl. Bypass
Bypass Valve Pressure Rating:	7.0 bar		

[Safety Warning](#)

Item Information +

CAD Drawings + Files +

Related Documents +



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:0080027275374)

AOG (Aircraft on Ground)

[1-949-851-4357](tel:1-949-851-4357)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

