



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In...](#) / 18P120QHBNXG122

High Pressure In-Line Filter - 18/28/38P Series

Part #: 18P120QHBNXG122



18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0-150 l/min	Indicator Type:	No indicator port
Length:	Length 1	Indicator Pressure Setting:	No indicator
Filter Element Type:	02QH High Strength Microglass	Connection Type:	Thread G $\frac{3}{4}$ "
Micron Rating:	20 μ m	Operating Temperature:	-40/+100°C
Seal Material:	Nitrile	Options:	No Bypass
Bypass Valve Pressure Rating:	No Bypass		

[Safety Warning](#)

Item Information

CAD Drawings + Files

Related Documents



Americas

USA, Canada, Mexico

cparker@support.parker.com
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)
AOG (Aircraft on Ground)
[1-949-851-4357](tel:1-949-851-4357)

-
- + Company Information
-
- + Global Operations
-
- + Help & Support
-
- + Follow Us :
-

© PARKER HANNIFIN CORP 2024

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

