



[Home](#)

[Products](#) ▾

[Help & Support](#)

[Industries](#)

[Where To Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In-...](#) / 18P205QBT1KG121

# High Pressure In-Line Filter - 18/28/38P Series

Part #: 18P205QBT1KG121



18/28/38P high pressure inline hydraulic oil filter series is a globally proven filter with optimised sizing covering flows up to 700 l/min and a pressure level up to 414 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Flow Rate:	0-110 l/min	Indicator Type:	Electrical NO/NC
Length:	Length 2	Indicator Pressure Setting:	2.5 bar
Filter Element Type:	05Q Microglass	Connection Type:	Thread G $\frac{3}{4}$ "
Micron Rating:	5 $\mu$ m	Operating Temperature:	-40/+100°C
Seal Material:	Nitrile	Options:	Standard, incl. Bypass
Bypass Valve Pressure Rating:	3.5 bar		

[Safety Warning](#)

## Item Information

## CAD Drawings + Files

## Related Documents



Americas

USA, Canada, Mexico

[cparker@support.parker.com](mailto:cparker@support.parker.com)  
[1-800-272-7537](tel:1-800-272-7537)

Europe

[00800 27 27 5374](tel:00800-27-27-5374)  
AOG (Aircraft on Ground)  
[1-949-851-4357](tel:1-949-851-4357)

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

