


[Home](#)
[Products](#) ▾

[Help & Support](#)
[Industries](#)
[Where To Buy](#)
[Home](#) / [Products](#) / [Hose, Piping and ...](#) / [Tubing](#) / [Fluoropolymer Tubing](#) / [PFA Tubing](#) / 204-1000100-NT-100

## PFA Tubing

Part #: 204-1000100-NT-100



PFA Tubing - Series 104 and 204 are used when temperature and clarity are both factors. PFA tubing withstands the same high-temperatures as PTFE tubing but, like FEP tubing, is very clear and available in long continuous lengths.

[View Series Page](#) ≡

[View Catalog\(s\)](#) ↗

[Share / Email](#) ↻

[Print](#) 🖨

### Technical Specifications

Standard Pack Qty (ft):	100.0	Minimum Burst Pressure:	900 psi, 62 bar
Tube Inside Diameter:	8	Maximum Operating Temperature:	500 °F, 260 °C
Order Size:	10MM	Minimum Operating Temperature:	-100 °F, -75 °C
Tube Outside Diameter:	10	Minimum Bend Radius:	2-3/4 inch, 70 mm
Tube Wall Thickness:	1	Compatible Fitting:	Metric Compression, TrueSeal™
Product Type:	Metric	Media:	Air, Chemicals, Water, Industrial Gases
Specifications Met:	ASTM D3307, FDA 21 CFR 177.1550, UL 94 V-0, USP Class VI	Color:	Clear
Application:	Air, Flow Monitoring, Gas Sampling, Semiconductor, Fluid Transfer, Laboratory, Steam Plant	Weight:	0.041 lb/ft, 0.061 kg/m
Tube Inside Diameter:	0.315 inch, 8 mm	Tube Material:	Perfluoroalkoxy Alkanes (PFA)
Tube Outside Diameter:	0.394 inch, 10 mm	Length per Package:	30.5 m, 100 ft
Maximum Operating Pressure:	100 psi, 7 bar	Product Type:	Metric

[⚠ Safety Warning](#)

### Item Information

### CAD Drawings + Files

## Related Documents



### Americas

USA, Canada, Mexico

[cparker@support.parker.com](mailto:cparker@support.parker.com)  
[1-800-272-7537](tel:1-800-272-7537)

### Europe

[00800 27 27 5374](tel:00800-27-27-5374)

**AOG (Aircraft on Ground)**

[1-949-851-4357](tel:1-949-851-4357)

---

+ Company Information

---

+ Global Operations

---

+ Help & Support

---

+ Follow Us :

---

© PARKER HANNIFIN CORP 2024

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



