

**Home** 

**Products** 

Support

**Industries** 

**Services** 

**Solutions** 

Where to Buy

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure In-... / 22PD110QHBPXR202

## **High Pressure In-Line Duplex Filter - 22PD-32PD Series**

Part #: 22PD110QHBPXR202







The 22PD-32PD Series High Pressure Duplex Filters are specially designed to offer continuous operation, even during element change.

View Series Page 

Share / Email 

Print 

Pr

### **Technical Specifications**

Brand: Flow Rate: 0 to 80 l/min Bypass Valve Pressure No bypass

Hydraulic & Industrial Process Filtration Division:

Division EMEA

Industrial Manufacturing Equipment Industry:

Off-Road Transport Connection Type: 11/4" SAE-3000M Application: Hydraulic Filtration Filter Element Type: 10QH High Collapse

Micron Rating: 10 µm

Technology: Filtration, Hydraulics Hydraulic Filter **Product Type:** 

▲ Safety Warning

Rating:

Options: No Bypass

Indicator Type: No indicator, port plugged

**Product Series:** 22PD-32PD Iron/Steel Housing Material: Indicator Pressure Setting: No indicator Mounting Type: Inline Seal Material: Nitrile

Mineral and vegetable oils and some synthetic For Fluid Type:

Operating Pressure: Up to 210 bar / 3045 psi

Operating Temperature: -40 / +100 °C Maximum Flow Rate: 210 L/min

Seal Material: Nitrile of Fluoroelastomer

#### Item Information

The 22PD-32PD Series is a high pressure filter with a wide application capability. It is designed to offer continuous operation during element

The 22PD-32PD Series utilizes a duplex design with integrated balancing valve and vent ports. A changeover valve operates on the upstream side of the filter, ensuring continuous filtration and a contamination free system.

Glass fibre filtration media is applied as standard.

#### **Product Features:**

- 22PD-32PD utilizes a duplex design with integrated balancing valve and vent ports.
- · Microglass III glass fibre media is standard.
- $\bullet$  Maximum pressure 210 bar. Maximum flow 260 l/min.
- Designed to offer continuous operation during element change.

#### **Typical Applications:**

- Ship steering systems
- Continuously operating industrial systems
- High pressure, high flow flushing systems

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

# CAD Drawings + Files Related Documents +



**Parker Sales Company UK** 

#### psc.uk.webform@support.parker.com +44 (0)1926 317878

+	Company	Inform	ation

+ Global Operations

+ Help & Support

+ Follow Us:

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS