

[Home](#)

[Products](#)

[Support](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Replacement Filte...](#) / [Liquid Filter Ele...](#) / [Clariflow-WG Plea...](#) / 25-10120-001-11-WG

Clariflow-WG Pleated Membrane Filter Cartridge | Water service grade hydrophilic PES membrane

Where to Buy
Part #: 25-10120-001-11-WG



Clariflow water service grade cartridges are cost-effective alternatives to Clariflow E and G grade cartridges for the filtration of a variety of aqueous liquids.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications -

Brand:	Parker	Core Type:	Polypropylene
Seal Material:	EPDM	Micron Rating (µm):	0.1
Industry:	Food and Beverage	Hose Reinforcement Material & Structure:	Polypropylene
Function:	Clarification/Prefiltration/Polishing	Flow Rate:	1.3GPM/PSID per 10 inch cartridge equivalent for 0.1
Media:	PES (Polyethersulfone)	End Cap Configuration:	DOE
Secondary Seal:	5mm thick gaskets	Style:	No Insert
Filter Construction:	Pleated Membrane	Length (inch):	20
Outside Diameter:	2.75 inch		
End Cap Material:	Polypropylene		

[Safety Warning](#)

Item Information -

The Clariflow-WG Pleated Membrane Filter Cartridge is built around a unique polyethersulfone (PES) membrane that is inherently hydrophilic, and contains no added surfactants or wetting agents. It delivers clean filtrates, flow rates, extended service life and excellent resistance to hydrolysis. Water Service cartridges are fabricated under cleanroom conditions.

CAD Drawings + Files +

Related Documents +

Parker Company UK



technicalsupport@support.parker.com

+44 (0)1926 317878

[Home](#)

Products

+ Company Information

Support

+ Global Operations

Industries

+ Help & Support

Services

+ Follow Us :

Solutions

Where to Buy

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
