

[Home](#)

[Products](#)

[Support](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Replacement Filte...](#) / [Liquid Filter Ele...](#) / [Clariflow-WG Plea...](#) / 25-10320-002-2-WG

Clariflow-WG Pleated Membrane Filter Cartridge | Water service grade hydrophilic PES membrane

Where to Buy
Part #: 25-10320-002-2-WG



Clariflow water service grade cartridges are cost-effective alternatives to Clariflow E and G grade cartridges for the filtration of a variety of aqueous liquids.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Filter Construction:	Pleated Membrane	Outside Diameter:	2.75 inch
Core Type:	Polypropylene	Hose Reinforcement Material & Structure:	Polypropylene
Brand:	Parker	Secondary Seal:	N/A
End Cap Material:	Polypropylene	Micron Rating (µm):	0.2
Flow Rate:	2.6GPM/PSID per 10 inch cartridge equivalent for 0.2	Seal Material:	S7442
Media:	PES (Polyethersulfone)	End Cap Configuration:	222 O-Ring/Flat Cap
Function:	Clarification/Prefiltration/Polishing	Style:	No Insert
Industry:	Food and Beverage	Length (inch):	20

[Safety Warning](#)

Item Information

The Clariflow-WG Pleated Membrane Filter Cartridge is built around a unique polyethersulfone (PES) membrane that is inherently hydrophilic, and contains no added surfactants or wetting agents. It delivers clean filtrates, flow rates, extended service life and excellent resistance to hydrolysis. Water Service cartridges are fabricated under cleanroom conditions.

CAD Drawings + Files

Related Documents

Parker Company UK



technicalsupport@support.parker.com

+44 (0)1926 317878

[Home](#)

Products

+ [Company Information](#)

Support

+ [Global Operations](#)

Industries

+ [Help & Support](#)

Services

+ [Follow Us :](#)

Solutions

Where to Buy

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
