

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Replacement Filte...](#) / [Liquid Filter Ele...](#) / [Clariflow-G Pleat...](#) / 25-10710-004-1-G

[Services](#)
[Solutions](#)
Clariflow-G Pleated Membrane Filter Cartridge | General grade Hydrophilic PES membrane

[Where to Buy](#)

Part #: 25 10710 004 1 G



Clariflow® General grade filter cartridges are designed for general-purpose use in the filtration of high-purity liquids and aqueous chemicals.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Brand:	Parker	Outside Diameter:	2.75 inch
Flow Rate:	4.8gpm/psid per 10 inch cartridge equivalent for 0.45um	Hose Reinforcement Material & Structure:	Polypropylene
Filter Construction:	Pleated Membrane	Seal Material:	EPDM
Media:	PES (Polyethersulfone)	Secondary Seal:	N/A
Core Type:	Polypropylene	Micron Rating (µm):	0.45
Function:	Clarification/Prefiltration/Polishing	End Cap Configuration:	226 O-Ring/Fin
End Cap Configuration:	Polypropylene	Style:	No Insert
Industry:	Industrial	Length (inch):	10

[Safety Warning](#)

Item Information

Clariflow® General grade filter cartridges are designed for general-purpose use in the filtration of high-purity liquids and aqueous chemicals. The mirrored-anisotropic Polyethersulfone (PES) membrane is inherently hydrophilic and has a pore morphology that delivers exceptionally high flow rates.

Because there are no added surfactants or wetting agents, and the support layers and structure are all-polypropylene, the filter exhibits low extractables, broad chemical compatibility and good resistance to hydrolysis.

The Clariflow General Grade Filter Cartridge is available in absolute ratings of 0.04, 0.1, 0.2, 0.45, 0.65 and 0.8µm pore sizes.

Features/Benefits

- High flow rate reduces processing time
- Broad chemical compatibility allows use in most applications
- Low differential pressure reduces system wear and tear

Applications

- Chemical filtration
- Liquid clarification filtration
- Recirculating fluid filtration
- General use water filtration
- Deionized water system filtration

[Home](#)

[Products](#)

Related Documents



[Support](#)

[Industries](#)



[Services](#)

[Solutions](#) Sales Company UK

usa@parker.com
uk@parker.com
webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

[+ Company Information](#)

[+ Global Operations](#)

[+ Help & Support](#)

[+ Follow Us :](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
