

Clariflow-E Pleated Membrane Filter Cartridges | Hydrophilic PES membrane for aqueous applications

Part #: 25-10740-001-4-E



Clariflow® -E filter cartridges are optimized for use in microelectronics applications such as DI water and aqueous-based chemicals in the removal of both organic and inorganic particulates.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	1.8gpm/psid Per 10 inch cartridge equivalent for 0.1um	Outside Diameter:	2.75 inch
Filter Construction:	Pleated Membrane	Hose Reinforcement Material & Structure:	Polypropylene
Media:	PES (Polyethersulfone)	Seal Material:	Viton
Core Type:	Polypropylene	Secondary Seal:	N/A
Brand:	Parker	Micron Rating (µm):	0.1
Function:	Clarification/Prefiltration/Polishing	End Cap Configuration:	226 O-Ring/Fin
End Cap Material:	Polypropylene	Length (inch):	40
Industry:	Microelectronics	Style:	No Insert

[Safety Warning](#)

Item Information

Clariflow® -E filter cartridges are optimized for use in microelectronics applications such as DI water and aqueous-based chemicals. The unique mirrored-anisotropic PES (Polyethersulfone) filter membrane has exceptionally high flow rates and on-stream lifetime while providing consistent removal of both organic and inorganic particulates.

The combination of hydrophilic PES filter membrane and a high-purity, all-polypropylene support structure results in a very low level of ionic and organic extractables, broad chemical compatibility, and resistance to particle shedding.

Every filter cartridge is fabricated in a clean room environment, pre-flushed with 18 megohm-cm ultrapure DI water, and 100% integrity tested in an ISO-certified facility.

Features/Benefits

- High-retention hydrophilic membrane
- High flow rate
- Broad chemical compatibility for multiple applications
- Long on-stream life
- 100% integrity tested

Applications

- BOE filtration
- Dilute HF filtration
- POU DI rinse filtration
- Bulk DI water systems filtration
- Copper plating filtration
- Ni plating filtration
- Hard disk wash process filtration
- Filtration of other dilute acids and bases

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44201926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

