

Clariflow-WG Pleated Membrane Filter Cartridge | Water service grade hydrophilic PES membrane

Part #: 25-10H20-002-2-WG



Clariflow water service grade cartridges are cost-effective alternatives to Clariflow E and G grade cartridges for the filtration of a variety of aqueous liquids.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Brand:	Parker	Hose Reinforcement Material & Structure:	Polypropylene
Industry:	Food and Beverage	Flow Rate:	2.6GPM/PSID per 10 inch cartridge equivalent for 0.2
Function:	Clarification/Prefiltration/Polishing	Micron Rating (µm):	0.2
Media:	PES (Polyethersulfone)	End Cap Configuration:	213 O-Ring/Recessed End Cap
Filter Construction:	Pleated Membrane	Seal Material:	S7442
Secondary Seal:	N/A	Style:	No Insert
Outside Diameter:	2.75 inch	Length (inch):	20
End Cap Material:	Polypropylene		
Core Type:	Polypropylene		

[Safety Warning](#)

Item Information

The Clariflow-WG Pleated Membrane Filter Cartridge is built around a unique polyethersulfone (PES) membrane that is inherently hydrophilic, and contains no added surfactants or wetting agents. It delivers clean filtrates, flow rates, extended service life and excellent resistance to hydrolysis. Water Service cartridges are fabricated under cleanroom conditions.

CAD Drawings + Files





Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

