

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Replacement Filte...](#) / [Liquid Filter Ele...](#) / [Clariflow-E Pleat...](#) / 25-A0310-001-5-E

[Services](#)  
[Solutions](#)

# Clariflow-E Pleated Membrane Filter Cartridges | Hydrophilic PES Membrane for aqueous applications

[Where to Buy](#)

Part #: 25 A0310 001 5 E



Clariflow® -E filter cartridges are optimized for use in microelectronics applications such as DI water and aqueous-based chemicals in the removal of both organic and inorganic particulates.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Brand:	Parker	Core Type:	Polypropylene
Industry:	Microelectronics	Micron Rating (µm):	0.1
Function:	Clarification/Prefiltration/Polishing	Hose Reinforcement Material & Structure:	Polypropylene
Style:	1/2" Shortened on 222 Fitting	Flow Rate:	1.8gpm/psid Per 10 inch cartridge equivalent for 0.1µm
Media:	PES (Polyethersulfone)	End Cap Configuration:	222 O-Ring/Flat Cap
Filter Construction:	Pleated Membrane	Seal Material:	FEP Encapsulated Viton
Secondary Seal:	N/A	Length (inch):	10
Outside Diameter:	2.75 inch		
End Cap Material:	Polypropylene		

[Safety Warning](#)

## Item Information

Clariflow® -E filter cartridges are optimized for use in microelectronics applications such as DI water and aqueous-based chemicals. The unique mirrored-anisotropic PES (Polyethersulfone) filter membrane has exceptionally high flow rates and on-stream lifetime while providing consistent removal of both organic and inorganic particulates.

The combination of hydrophilic PES filter membrane and a high-purity, all-polypropylene support structure results in a very low level of ionic and organic extractables, broad chemical compatibility, and resistance to particle shedding.


Every filter cartridge is fabricated in a clean room environment, pre-flushed with 18 megohm-cm ultrapure DI water, and 100% integrity tested in an ISO-certified facility.


Features/Benefits

- High-retention hydrophilic membrane
- High flow rate
- Broad chemical compatibility for multiple applications
- Long on-stream life
- 100% integrity tested

Applications

- BOE filtration
- Dilute HF filtration

- POU/PLI filtration
-  systems filtration
- Copper plating filtration
- Ni plating filtration
- Hard disk wash process filtration
- Filtration of other dilute acids and bases



[Home](#)

[Products](#)

[Support](#) **CAD Drawings + Files**



[Industries](#)

[Services](#) **Related Documents**



[Solutions](#)

[Where to Buy](#)



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)

+44 (0)1926 317878

+ [Company Information](#)

+ [Global Operations](#)

+ [Help & Support](#)

+ [Follow Us :](#)

© PARKER HANNIFIN CORP 2024

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---