

Clariflow-WG Pleated Membrane Filter Cartridge | Water service grade hydrophilic PES membrane

Part #: 25-10840-002-2-WG



Clariflow water service grade cartridges are cost-effective alternatives to Clariflow E and G grade cartridges for the filtration of a variety of aqueous liquids.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|----------------------|---------------------------------------|--|--|
| Brand: | Parker | Hose Reinforcement Material & Structure: | Polypropylene |
| Industry: | Food and Beverage | Flow Rate: | 2.6GPM/PSID per 10 inch cartridge equivalent for 0.2 |
| Function: | Clarification/Prefiltration/Polishing | Micron Rating (µm): | 0.2 |
| Media: | PES (Polyethersulfone) | End Cap Configuration: | 222 O-Ring/Fin |
| Filter Construction: | Pleated Membrane | Seal Material: | S7442 |
| Secondary Seal: | N/A | Length (inch): | 40 |
| Outside Diameter: | 2.75 inch | Style: | No Insert |
| End Cap Material: | Polypropylene | | |
| Core Type: | Polypropylene | | |

[Safety Warning](#)

Item Information

The Clariflow-WG Pleated Membrane Filter Cartridge is built around a unique polyethersulfone (PES) membrane that is inherently hydrophilic, and contains no added surfactants or wetting agents. It delivers clean filtrates, flow rates, extended service life and excellent resistance to hydrolysis. Water Service cartridges are fabricated under cleanroom conditions.

CAD Drawings + Files



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

