

[Home](#)[Products](#)[Support](#)[Industries](#)[Services](#)[Solutions](#)[Where to Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure Fil...](#) / 30P202QBM3KG161

High Pressure Filters - 15P/30P Series

Part #: 30P202QBM3KG161



High pressure hydraulic filters for flow rates up to 200 l/min, with a maximum flow rate of 207 bar.

[View Series Page](#)[View Catalog\(s\)](#)[Share / Email](#)[Print](#)

Technical Specifications

Filter Element Type:	Q002 microglass		
Filter Type:	30P		
Port Size:	G1		
Length:	Length 2	Application:	
Flow Rate:	0 to 150 l/min		
Division:	Hydraulic and Industrial Process Filtration		
Brand:	EMEA		
Technology:	Parker	Pressure Rating:	2.5 bar
Product Type:	Filtration	Seal Material:	Nitrile
Filter Type:	Hydraulic Filter	Bypass Valve Pressure Rating:	3.5 bar
Product Series:	High Pressure Filter	Options:	None
	15P/30P Series		

[Safety Warning](#)

Item Information

Modern high pressure hydraulic systems are demanding. Better controls and long component life are expected. To deliver the high standards of performance, hydraulic components are built with tighter tolerances which increases their sensitivity to contamination.

That's where Parker high pressure filters come into play. They filter out ingressed contamination before it jams a valve or scores a cylinder. They block pump generated debris before it gets to servo or proportional valves. Parker pressure filters are a key ingredient in meeting today's system

demands.

Put your hydraulic systems in the care of Parker Filtration. We are committed to designing and building the best filters available to industry.

Features

- Compact aluminium housing
- Two head sizes and two bowl lengths
- Large ports and wide flow paths
- Microglass III replacement elements
- Visual, electrical and electronic indicators available

Benefits

- Reliable and continuous operation both in mobile and industrial applications
- Efficient filtration
- Right filter for each application
- Higher flow rates possible
- Less lost energy
- Great performance value
- Reliable performance throughout element life
- Reduces downtime, maximises element life
- Optimise element life, prevent bypassing
- Matches your system electrical connections

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com

[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

