



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure Inl... / 30P210QHBM2KS162

## High Pressure Inline/Duplex Filter 15P/30P/30PD Series

Part #: 30P210QHBM2KS162



The Parker 15P/30P Series is a high pressure all aluminum filter assembly that comes in a variety of options. The 15P/30P Series has a rated fatigue pressure of up to 2,000psi and flow rate up to 45gpm.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

### Technical Specifications

Mounting Style:	inline	Indicator Pressure Setting:	50 PSI (3.5 bar)
Port Connection Type:	SAE-16 ports	Options:	no bypass
Seal Material:	nitrile	Housing Material:	bowl - impacted aluminum (6061-T6, black powderpainted exterior); head - extruded aluminum (anodized 6061-T6)
Flow Rate:	55 GPM (208 LPM)	Filter Element Type:	cartridge
Indicator Type:	visual automatic reset	For Fluid Type:	Suitable for use with mineral and vegetable oils, and some synthetic oils. For other fluids, please email Technical Support at <a href="mailto:HF.Techsupport@support.parker.com">HF.Techsupport@support.parker.com</a> or call 800-253-1258
Micron Rating:	10Q high collapse microglass (2000 psid)	Maximum Operating Temperature:	225 F (107 C)
Options:	no bypass	Weight:	8.7 lb (3.9 kg)
Bypass Valve Pressure Rating:	50 psid (3.5 bar)	Compatible Element:	932633Q
Pressure Rating:	3000 psi (206.9 bar)	Product Style:	Hydraulic Filter
Flow Rate:	55 GPM (208 LPM)	Product Type:	Hydraulic Filter
Micron Rating:	10Q high collapse microglass (2000 psid)		
Seal Material:	nitrile		
Port Type:	SAE-16 ports		
Indicator Type:	visual automatic reset		

[Safety Warning](#)



## Item Information



The Parker 15P/30P Series is a high pressure all aluminum filter assembly that comes in a variety of options. The 15P/30P Filter Series has a rated fatigue pressure of up to 2,000psi. With its high pressure capability and lightweight design, the 15P/30P Series is an ideal solution for mobile applications. Single and double length bowls are available to cover a wide range of flow rates up to 45gpm. The duplex option comes with a diverter valve to allow for element change out on critical applications where the system cannot be shut down. Various seal, indicator, and porting options make it easy for users to integrate the 15P/30P Series into their hydraulic system.

## CAD Drawings + Files



## Related Documents



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

**ENGINEERING YOUR SUCCESS.**

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



