

[Home](#)[Products](#)[Support](#)[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure Inl...](#) / 30P210QVM2KS161[Services](#)[Solutions](#)[Part #:](#) 30P210QVM2KS161[Where to Buy](#)

High Pressure Inline/Duplex Filter 15P/30P/30PD Series



The Parker 15P/30P Series is a high pressure all aluminum filter assembly that comes in a variety of options. The 15P/30P Series has a rated fatigue pressure of up to 2,000psi and flow rate up to 45gpm.

[View Series Page](#)[View Catalog\(s\)](#)[Share / Email](#)[Print](#)

Technical Specifications

Mounting Style:	inline	Indicator	
Port Connection		Pressure	50 PSI (3.5 bar)
Type:	SAE-16 ports	Setting:	
Flow Rate:	55 GPM (208 LPM)	Options:	none
Indicator Type:	visual automatic reset	Housing	bowl - impacted aluminum (6061-T6, black powderpainted exterior); head - extruded aluminum (anodized 6061-T6)
Micron Rating:	10Q microglass	Material:	
Seal Material:	Fluorocarbon	Filter Element	cartridge
Options:	none	Type:	
Bypass Valve		For Fluid Type:	Suitable for use with mineral and vegetable oils, and some synthetic oils. For other fluids, please email Technical Support at HFF.techsupport@support.parker.com or call 800-253-1258
Pressure Rating:	50 psid (3.5 bar)		
Pressure Rating:	3000 psi (206.9 bar)	Maximum	
Flow Rate:	55 GPM (208 LPM)	Operating	275 F (135 C)
Micron Rating:	10Q microglass	Temperature:	
Seal Material:	Fluorocarbon	Weight:	8.7 lb (3.9 kg)
Port Type:	SAE-16 ports	Compatible	
Indicator Type:	visual automatic reset	Element:	932630Q
		Product Style:	Hydraulic Filter
		Product Type:	Hydraulic Filter

[Safety Warning](#)

Item Information

The Parker 15P/30P Series is a high pressure all aluminum filter assembly that comes in a variety of options. The 15P/30P Filter Series has a rated fatigue pressure of up to 2,000psi. With its high pressure capability and lightweight design, the 15P/30P Series is an ideal solution for mobile applications. Single and double length bowls are available to cover a wide range of flow rates up to 45gpm. The duplex option comes with a diverter valve to allow for element change out on critical applications where the system cannot be shut down. Various seal, indicator, and porting options make it easy for users to integrate the 15P/30P Series into their hydraulic system.

[Home](#)

[Related Documents](#)

[Products](#)



[Support](#)

[Industries](#)

[Services](#)


[Solutions](#)

[Parker Sales Company UK](#)


[Where to Buy](#)

pse-uk-webform@support.parker.com

[+44 \(0\)1926 317878](tel:+441926317878)

 [Company Information](#)

 [Global Operations](#)

 [Help & Support](#)

 [Follow Us :](#)

© PARKER HANNIFIN CORP 2024

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
