

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In...](#) / 32PD105QBM3KR241

High Pressure In-Line Duplex Filter - 22PD-32PD Series

[Services](#)

Part #: 32PD105QBM3KR241

[Where to Buy](#)



The 22PD-32PD Series High Pressure Duplex Filters are specially designed to offer continuous operation, even during element change.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 160 l/min	Product Type:	Hydraulic Filter
Brand:	Parker	Indicator Type:	Visual
Division:	Hydraulic & Industrial Process Filtration Division EMEA	Product Series:	22PD-32PD
Bypass Valve Pressure Rating:	3.5 bar	Housing Material:	Iron/Steel
Industry:	Industrial Manufacturing Equipment Off-Road Transport	Indicator Pressure Setting:	2.5 bar
Connection Type:	1½" SAE-3000M	Mounting Type:	Inline
Application:	Hydraulic Filtration	Seal Material:	Nitrile
Filter Element Type:	05Q Microglass	For Fluid Type:	Mineral and vegetable oils and some synthetic oils
Micron Rating:	5 µm	Operating Pressure:	Up to 210 bar / 3045 psi
Technology:	Filtration, Hydraulics	Operating Temperature:	-40 / +100 °C
Options:	With Bypass	Maximum Flow Rate:	210 L/min
		Seal Material:	Nitrile of Fluoroelastomer

[Safety Warning](#)

Item Information

The 22PD-32PD Series is a high pressure filter with a wide application capability. It is designed to offer continuous operation during element change.

The 22PD-32PD Series utilizes a duplex design with integrated balancing valve and vent ports. A changeover valve operates on the upstream side of the filter, ensuring continuous filtration and a contamination free system.

Glass fibre filtration media is applied as standard.


Product Features:

- 22PD-32PD utilizes a duplex design with integrated balancing valve and vent ports.
- Microglass III glass fibre media is standard.
- Maximum pressure 210 bar. Maximum flow 260 l/min.
- Designed to offer continuous operation during element change.

Typical Applications:



- Cleaning systems
- Operating industrial systems
- High pressure, high flow flushing systems



Home

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

Products

CAD Drawings + Files



Support

Industries

Related Documents



Services

Solutions

Where to Buy



Parker Sales Company UK

psc.uk.webform@support.parker.com

[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

