

<u>Home</u>

Products

Support

Industriesoducts / Filters, Collecto... / Replacement Filte... / Liquid Filter Ele... / Fulflo Honeycomb ... / 39R20S

শটাদীত Honeycomb Wound Filter Cartridges | Multi-purpose design with প্রাটাদানা 90% efficiency from 0.5-150 micron

Where to Buy Part #: 39R20S



Parker has been a leader in filter media innovation and performance since we first invented the Honeycomb[™] Filter Tube over 65 years ago. Parker has the world's largest manufacturing capacity for wound filter cartridges, offering superior quality.

View Series Page ∷	View Catalog(s)
Share / Email 🏞	Print 🖶

Technical Specifications

Micron Rating (µm): Industry: Filter Construction: End Cap Finish: Core Cover Material: Brand: Function: Core Type: Media: Filter Construction: 1 Food and beverage Cotton FDA Grade No end treatment No core cover domnick hunter Clarification/Prefiltration/Polishing 316 Stainless steel Cotton FDA Grade Wound

ß

Inside Diameter: Specifications Met: Flow Rate: End Cap Material: Packaging: End Cap Configuration: Seal Material: Length (inch): Outside Diameter (inch): 1 inch FDA 3 GPM per 10 inch No end cap STANDARD PACKAGING DOE No gasket 20 2 7/16

▲ Safety Warning

Item Information

Parker has been a leader in filter media innovation and performance since we first invented the Honeycomb[™] Filter Tube over 65 years ago. Parker has the world's largest manufacturing capacity for wound filter cartridges, offering superior quality along with technical, engineering and marketing support.

Effective removal ratings at nominal 90% efficiency from $0.5\mu m$ to $150\mu m$.

Features/Benefits

- · A broad range of media provide excellent compatibility with a variety of organic solvents, animal, petroleum and vegetable oils
- · Optional core covers and end treatments assure fiber migration control
- Multiple length filter cartridges minimize change-out time, eliminate spacers and are available to fit competitive filter vessels

• FDA grade polypropylene (DOE only) filter cartridges certified to ANSI/ NSF61 standard for contact with drinking water components

· Continuous strand winding geometry provides performance consistency



 extended center core option eliminates the need for cartridge guides in all competitive and Fulflo® multi-cartridge vessels extender is available for polypropylene cores O-ring/end cap options available O-ring/end cap options available Provide cap options avail	
CAD Drawings + Files + Related Documents +	



Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS



<u>Home</u>

- Products
- Support

Industries

Services

Solutions

Where to Buy