

[Home](#)[Products](#)[Support](#)[Industries](#)[Services](#)[Solutions](#)[Where to Buy](#)

[Home](#) / [Products](#) / [Filters, Collecto...](#) / [Replacement Engin...](#) / [Hydraulic Filter ...](#) / [Replacement Eleme...](#) / 403488

## Replacement Elements - High Pressure 12S Series

Part #: 403488



double

[View Series Page](#)[View Catalog\(s\)](#)[Share / Email](#)[Print](#)

### Technical Specifications

Micron Rating:	20QH microglass	Length:	double
Seal Material:	Ethylene Propylene	Compatible Series:	12S
Filter Element Type:	Cartridge	For Fluid Type:	Mineral, Petroleum and Polyalphaolefin (PAO) based fluids
		Product Type:	Hydraulic Filter

[Safety Warning](#)

### Item Information

The Parker 12S Series is an ultra high pressure stainless steel filter designed with the latest in filtration technology.

Using Parker 12S Series high efficiency replacement elements guarantees Parker's quality of filtration, directly impacting your system's fluid cleanliness and performance. Using knock-off aftermarket elements with unknown media quality may save initial cost, but can increase overall costs by requiring more frequent element servicing and potentially causing catastrophic system downtime. Protect your investment by always buying genuine Parker replacement elements.

Available in Single and Double length. All elements are rated at 2000 psid collapse, and are available in several micron ratings, (2, 5, 10, and 20 micron). These replacement elements are constructed to provide the quality of filtration that Parker is known for. For ordering, please refer to the "How to Order" section of the literature or contact a Parker Representative.

### CAD Drawings + Files





Parker Sales Company UK

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING **YOUR** SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

