

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Medium Pressure I...](#) / 40CN210QBM3KG201

Medium Pressure Inline Filters CN Series

[Solutions](#)

Part #: 40CN210QBM3KG201

[Where to Buy](#)



The CN Series is a compact, cost effective, medium pressure filter designed with coreless filtration technology. CN Series bowl features a permanently fixed core designed to reduce solid waste and minimize disposal costs with every element change out.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Technical Specifications

Flow Rate:	240 l/min (66 gal/min)	Bypass Valve Pressure Rating:	3.5 bar (50 psi)
Filter Element Type:	10Q Microglass	Options:	No drain
Seal Material:	Nitrile	Micron Rating:	10 µm
Port Connection Type:	G1 1/4"	Indicator Type:	Visual Automatic Reset
Specifications Met:	n/a	Indicator Pressure Setting:	2.5 bar

[Safety Warning](#)

Item Information

Compressor Lube Oil
 Off-line Filter Loops
 Machine Tools (Automotive Standard)
 Hydrostatic Drive Charge Pumps
 Mobile Equipment
 Pilot Lines for Servo Controls
 Oil Patch Drilling Equipment
 Injection Molding

This partial list of applications for Parker CN series filters has a common factor, the need for an economical, medium pressure range filter with excellent fatigue pressure ratings. Prior to the availability of the CN filter, applications such as those listed were restricted by limitations of a spin-on can, or forced into the higher cost range of high pressure filters.

The CN series fills this gap, and now with the newly increased fatigue rating from 550 to 800 psi, the applications are expanded.

Features

- 800 psi fatigue rating (eight times that of a spin-on)
- Diametral (side) seal between head and bowl
- Dust Seal

- **Class elements**
- **Complete performance data disclosure**
- **Visual, electrical or electrical/visual indicators available**

Home

- **Advantages**
- **Products** Ability to provide reliable service under tough cyclic operating conditions
- **Support** Can be utilized in applications where high pressure filters may have been only option

- **Industries** Improved reliability in cyclic applications

- **Industries** Reduced importance of bowl torque

- **Industries** contamination from building up on bowl / head threads

- **Industries** Low profile, lightweight and durable

- **Industries** Layered design produced high capacity and efficiency

- **Industries** Reduces pleat bunching, keeps performance consistent

- **Industries** Element information is provided in an easy-to-compare format

- **Industries** Check element condition at a glance

- **Industries** Right fit for the application

Benefits

- Reduced downtime due to premature filter failures
- Reduced costs, better "fit" for the application
- No downtime, no leaks
- Performs with "real world" service
- Easier service, no galling
- Less weight, smaller envelop and cleaner appearance
- Great performance value
- Reliable performance throughout element life
- Reduces downtime, maximizes element life
- No hidden deficiencies
- Easy selection of proper filtration
- Optimize element life, prevent bypassing
- Matches your system electrical connections

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
 +44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
