

Home

Products

Support

Industries

Services

Solutions

Where to Buy

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / Medium Pressure I... / 40CN220QEBE2GS164

Medium Pressure Inline Filters CN Series

Part #: 40CN220QEBE2GS164







The CN Series is a compact, cost effective, medium pressure filter designed with coreless filtration technology. CN Series bowl features a permanently fixed core designed to reduce solid waste and minimize disposal costs with every element change out.

View Series Page

View Catalog(s)

✓

Share / Email 🕈 Print 🖶

Technical Specifications

Flow Rate: 70 gpm (265 lpm)

Mounting Style: Inline

Filter Element Type: 200 Microglass
Pressure Rating: 1000 psi (69 bar)

Seal Material: Nitrile

Port Connection Type: SAE-16 straight threads

Specifications Met: n/a

Bypass Valve Pressure
Rating:
Options:

25 psi (1.7 bar)
Drain port

Port Type: SAE-16 straight threads

Indicator Type:

Indicator Pressure Setting: Housing Material:

For Fluid Type:

Maximum Operating Temperature: Weight:

Compatible Element: Product Style: Product Type: Electrical/Visual (DIN43650 Hirschman style

connection) 25 psi (1.7 bar) Aluminum

Mineral, Petroleum and Polyalphaolefin (PAO)

based fluids

225 F (107 C)
5.5 lbs (2.49 kg)
936712Q
Hydraulic Filter
Hydraulic Filter

⚠ Safety Warning

Item Information

Compressor Lube Oil Off-line Filter Loops Machine Tools (Automotive Standard) Hydrostatic Drive Charge Pumps Mobile Equipment Pilot Lines for Servo Controls Oil Patch Drilling Equipment Injection Molding

This partial list of applications for Parker CN series filters has a common factor, the need for an economical, medium pressure range filter with excellent fatigue pressure ratings. Prior to the availability of the CN filter, applications such as those listed were restricted by limitations of a spin-on can, or forced into the higher cost range of high pressure filters.

The CN series fills this gap, and now with the newly increased fatigue rating from 550 to 800 psi, the applications are expanded.

Features

- · 800 psi fatigue rating (eight times that of a spin-on)
- · Diametral (side) seal between head and bowl
- · Dust Seal
- · Cast aluminum head
- · Standard Microglass elements
- · Complete performance data disclosure
- · Visual, electrical or electrical/visual indicators available

Advantages

- · Ability to provide reliable service under tough cyclic operating conditions
- · Can be utilized in applications where high pressure filters may have been only option
- · Proven reliability in cyclic applications
- · Reduced importance of bowl torque
- · Prevents contamination from building up on bowl / head threads
- · Low profile, lightweight and durable
- · Multi-layered design produced high capacity and efficiency
- · Reduces pleat bunching, keeps performance consistent
- · All pertinent information is provided in an easy-to-compare format
- · Check element condition at a glance
- · Right style for the application

Benefits

- · Reduced downtime due to premature filter failures
- · Reduced costs, better "fit" for the application
- · No downtime, no leaks
- · Performs with "real world" service
- · Easier service, no galling
- Less weight, smaller envelop and cleaner appearance
- · Great performance value
- · Reliable performance throughout element life
- · Reduces downtime, maximizes element life
- · No hidden deficiencies
- · Easy selection of proper filtration
- · Optimize element life, prevent bypassing
- · Matches your system electrical connections

_		_	rawings					4
(· /	41)	1)1	'AKC'	ınn	10	-	HI	ΔC
v	70	$\boldsymbol{\nu}$	αvv	IIIU				CO



Related Documents





Parker Sales Company UK

psc.uk.webform@support.parker.com +44 (0)1926 317878

- + Company Information
- + Global Operations
- + Help & Support
- + Follow Us:

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS