

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Medium Pressure I...](#) / 45M302QBPKG161

Medium Pressure In-Line Filter - 45M Series

[Solutions](#)

Part #: 45M302QBPKG161

[Where to Buy](#)



The 45M Series of medium pressure filters offer an ideal solution to the problem of protecting system components at lower pressures. The robust filter housing allows the 45M product to be applied in harsh environments.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|-------------------------------|--|------------------------|--|
| Port Connection Type: | G1 | Application: | Industrial Power Units, Mobile Construction Equipment, Forestry Equipment |
| Filter Element: | 02Q Microglass | Micron Rating: | 2 µm |
| Temperature Characteristics: | -40 / +100°C | Technology: | Hydraulics, Filtration |
| Flow Capacity: | 150 l/min | Indicator Type: | No indicator, port plugged |
| Indicator Pressure Setting: | No indicator | Product Type: | Hydraulic Filter |
| Brand: | Parker | Product Series: | 45M Series |
| Flow Rate: | 150 l/min | Options: | Standard |
| Division: | Hydraulic & Industrial Process Filtration Division EMEA | Seal Material: | Nitrile |
| Bypass Valve Pressure Rating: | 3.5 bar | For Fluid Type: | Hydraulic Oil |
| Connection Type: | G1 | Height: | 450 mm |
| Industry: | Industrial Manufacturing Equipment, Off-Road Machinery, Power Generation | Operating Pressure: | 40 bar |
| Filter Element Type: | 02Q Microglass | Operating Temperature: | Seal Material Nitrile: -40 to +100 °C, Seal Material Fluoroelastomer: -20 to +120 °C |
| | | Mounting Type: | Inline |
| | | Housing Material: | Iron/Steel |
| | | Specifications Met: | Degree of filtration determined by multipass test according to ISO 16889. |

[Safety Warning](#)

Item Information

The 45M/45 Eco Series utilizes a cast iron head and steel bowl design and can be specified with Microglass III or Ecoglass III filter media. Filter bowl is designed for rapid element replacement. ECO Series elements reduces waste by over 50% due to the reusable element core.

Features and Benefits

- Cast iron head and steel bowl offering reliable filtration in all conditions including engine rooms and mins
- Check element condition at a glance with visual, electrical or electronic indicators available to suit a wide range of applications
- Test points in the filter head for quick testing and maintenance

Coreless Microglass III replacement elements are available with Microglass III or Ecoglass III filter media:



Home

Reinforced Microglass III replacement elements have a multi-layered design for high capacity and efficiency for great performance and value throughout the life of the element.

Products

Ecoglass III:

Support

Coreless Ecoglass III replacement elements utilized a reusable element core which reduces waste by over 50% lowering replacement and disposal costs. Eco adaptors are available to retrofit coreless design to housings already installed.

Industries

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

Services

CAD Drawings + Files



Solutions

Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
