

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Medium Pressure I...](#) / 45M305QEBPKG241

Medium Pressure In-Line Filter - 45M Series

[Solutions](#)

Part #: 45M305QEBPKG241

[Where to Buy](#)



The 45M Series of medium pressure filters offer an ideal solution to the problem of protecting system components at lower pressures. The robust filter housing allows the 45M product to be applied in harsh environments.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

<p>Port Connection Type: G1½</p> <p>Temperature Characteristics: -40 / +100°C</p> <p>Filter Element: 05QE Ecoglass</p> <p>Flow Capacity: 210 l/min</p> <p>Indicator Pressure Setting: No indicator</p> <p>Brand: Parker</p> <p>Flow Rate: 210 l/min</p> <p>Division: Hydraulic & Industrial Process Filtration Division EMEA</p> <p>Bypass Valve Pressure Rating: 3.5 bar</p> <p>Connection Type: G1½</p> <p>Industry: Industrial Manufacturing Equipment, Off-Road Machinery, Power Generation</p> <p>Filter Element Type: 05QE Ecoglass</p>	<p>Application: Industrial Power Units, Mobile Construction Equipment, Forestry Equipment</p> <p>Micron Rating: 5 µm</p> <p>Technology: Hydraulics, Filtration</p> <p>Indicator Type: No indicator, port plugged</p> <p>Product Type: Hydraulic Filter</p> <p>Product Series: 45M Series</p> <p>Options: Standard</p> <p>Seal Material: Nitrile</p> <p>For Fluid Type: Hydraulic Oil</p> <p>Height: 450 mm</p> <p>Operating Pressure: 40 bar</p> <p>Operating Temperature: Seal Material Nitrile: -40 to +100 °C, Seal Material Fluoroelastomer: -20 to +120 °C</p> <p>Mounting Type: Inline</p> <p>Housing Material: Iron/Steel</p> <p>Specifications Met: Degree of filtration determined by multipass test according to ISO 16889.</p>
---	---

[Safety Warning](#)

Item Information

The 45M/45 Eco Series utilizes a cast iron head and steel bowl design and can be specified with Microglass III or Ecoglass III filter media. Filter bowl is designed for rapid element replacement. ECO Series elements reduces waste by over 50% due to the reusable element core.

Features and Benefits

- Cast iron head and steel bowl offering reliable filtration in all conditions including engine rooms and mins
- Check element condition at a glance with visual, electrical or electronic indicators available to suit a wide range of applications
- Test points in the filter head for quick testing and maintenance

Coreless filter media with Microglass III or Ecoglass III filter media:



Home

Reinforced Microglass III replacement elements have a multi-layered design for high capacity and efficiency for great performance and value throughout the life of the element.

Products

Ecoglass III:

Support

Coreless Ecoglass III replacement elements utilized a reusable element core which reduces waste by over 50% lowering replacement and disposal costs. Eco adaptors are available to retrofit coreless design to housings already installed.

Industries

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

Services

CAD Drawings + Files



Solutions

Related Documents



Related Products



Medium Pressure
Inline Hydraulic Oil
Filter - iProtect®
GMF Series



Parker Sales Company UK

psc.uk.webform@support.parker.com

+44 (0)1926 317878

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
