

[Home](#)
[Products](#)
[Support](#)
[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In...](#) / 70B202QHBPXX324

[Services](#)
[Solutions](#)

Part #: 70B202QHBPXX324
[Where to Buy](#)

High Pressure In-Line Filter - 70/70 Eco Series



High pressure inline hydraulic oil filter series is a proven filter concept, with multiple connection options up to 500l/min and pressures up to 420 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Flow Rate:	0 to 200 l/min		
Division:	Hydraulic and Industrial Process Filtration EMEA		
Brand:	Parker		
Indicator Pressure Setting:	No indicator		
Technology:	Filtration	Application:	Drilling machines Dumpers Hydraulic power units Mobile cranes Reach stackers Container handling equipment Cranes Excavators Crushing machines Propulsion systems Deck machinery Wind turbines Hydropower Servo controls
Seal Material:	Nitrile		
Bypass Valve Pressure Rating:	No by pass	Options:	Drain port
Product Series:	70/70 Eco Series	For Fluid Type:	Suitable for use with mineral and vegetable oils, and some synthetic oils.
Connection Type:	Side manifold	Operating Pressure:	420 bar
	Mining	Operating Temperature:	-40°C to +100°C
	Material handling		Head:
	Construction		Cast iron (GSI).
Industry:	Marine	Materials of Construction:	
	Power Generation		Bowl:
	Industrial Machinery		Steel. Max torque 40 Nm.
	Injection Moulding		

Safety Warning

Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The Parker 1100 is differential pressure indicator fitted to this series is unrivalled in its performance.



- Mobile working hydraulics
- Mobile drive system
- Injection moulding
- Servo controls
- Die casting
- Machine tools
- Industrial power units

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files +

Solutions

Related Documents +



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
