

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In-...](#) / 70B210QBPMX321F1

[Services](#)  
**High Pressure In-Line Filter - 70/70 Eco Series**

[Solutions](#)

Part #: 70B210QBPMX321F1  
[Where to Buy](#)



High pressure inline hydraulic oil filter series is a proven filter concept, with multiple connection options up to 500l/min and pressures up to 420 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

## Technical Specifications

Flow Rate:	0 to 420 l/min		Drilling machines
Division:	Hydraulic and Industrial Process Filtration EMEA		Dumpers
Indicator Pressure Setting:	No indicator		Hydraulic power units
Brand:	Parker		Mobile cranes
Technology:	Filtration	Application:	Reach stackers
Seal Material:	Nitrile		Container handling equipment
Bypass Valve Pressure Rating:	7.0 bar		Cranes
Product Series:	70/70 Eco Series		Excavators
	Mining		Crushing machines
	Material handling	For Fluid Type:	Propulsion systems
	Construction		Deck machinery
Industry:	Marine	Operating Pressure:	Wind turbines
	Power Generation		Hydropower
	Industrial Machinery	Operating Temperature:	Servo controls
	Injection Moulding		Suitable for use with mineral and vegetable oils, and some synthetic oils.
Connection Type:	Side manifold		420 bar
Options:	For HFC liquid	Materials of Construction:	-40°C to +100°C
			Head:
			Cast iron (GSI).
			Bowl:
			Steel. Max torque 40 Nm.

Safety Warning

## Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

**Industries**

**CAD Drawings + Files**



**Solutions**

**Related Documents**



**Where to Buy**



**Parker Sales Company UK**

[psc.uk.webform@support.parker.com](mailto:psc.uk.webform@support.parker.com)  
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

---