

[Home](#)
[Products](#)
[Support](#)
[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In...](#) / 70B310QEBPKX321

[Services](#)
[Solutions](#)

Part #: 70B310QEBPKX321
[Where to Buy](#)



High pressure inline hydraulic oil filter series is a proven filter concept, with multiple connection options up to 500l/min and pressures up to 420 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|-------------------------------|--|----------------------------|--|
| Division: | Hydraulic and Industrial Process Filtration EMEA | | |
| Flow Rate: | 0 to 300 l/min | | |
| Indicator Pressure Setting: | No indicator | | |
| Brand: | Parker | | |
| Seal Material: | Nitrile | Application: | Drilling machines Dumpers Hydraulic power units Mobile cranes Reach stackers Container handling equipment Cranes Excavators Crushing machines Propulsion systems Deck machinery Wind turbines Hydropower Servo controls |
| Technology: | Filtration | | |
| Product Series: | 70/70 Eco Series | | |
| Bypass Valve Pressure Rating: | 3.5 bar | | |
| | Mining Material handling Construction | For Fluid Type: | Suitable for use with mineral and vegetable oils, and some synthetic oils. |
| Industry: | Marine Power Generation Industrial Machinery Injection Moulding | Operating Pressure: | 420 bar |
| Connection Type: | Side manifold | Operating Temperature: | -40°C to +100°C |
| Options: | Standard | Materials of Construction: | Head: Cast iron (GSI). Bowl: Steel. Max torque 40 Nm. |

Safety Warning

Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

Industries

CAD Drawings + Files

Services



Solutions

Related Documents

Where to Buy



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
