

[Home](#)
[Products](#)
[Support](#)
[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In...](#) / 70L310QHVPXG202

[Services](#)
[Solutions](#)

Part #: 70L310QHVPXG202
[Where to Buy](#)

High Pressure In-Line Filter - 70/70 Eco Series



High pressure inline hydraulic oil filter series is a proven filter concept, with multiple connection options up to 500l/min and pressures up to 420 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

Division:	Hydraulic and Industrial Process Filtration EMEA		
Flow Rate:	0 to 430 l/min		
Brand:	Parker		
Indicator Pressure	No indicator		
Setting:	No indicator		
Seal Material:	Fluoroelastomer	Application:	Drilling machines Dumpers Hydraulic power units Mobile cranes Reach stackers Container handling equipment Cranes Excavators Crushing machines Propulsion systems Deck machinery Wind turbines Hydropower Servo controls
Technology:	Filtration		
Bypass Valve Pressure	No by pass		
Rating:	No by pass		
Product Series:	70/70 Eco Series		
	Mining		
	Material handling		
	Construction		
Industry:	Marine	For Fluid Type:	Suitable for use with mineral and vegetable oils, and some synthetic oils.
	Power Generation	Operating Pressure:	420 bar
	Industrial Machinery	Operating Temperature:	-20°C to +120°C
	Injection Moulding		
Connection Type:	G1¼"	Materials of	Head: Cast iron (GSI).
Options:	No by pass	Construction:	Bowl: Steel. Max torque 40 Nm.

[Safety Warning](#)

Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.
Industries

CAD Drawings + Files +

Solutions
Related Documents +
Where to Buy



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
