

Home

Products

Support

Industries

Services

Solutions

Where to Buy

Home / Products / Filters, Collecto... / Filter Assemblies... / Hydraulic Filters / High Pressure In-... / 70L405QHBT1NG242

High Pressure In-Line Filter - 70/70 Eco Series

Part #: 70L405QHBT1NG242







High pressure inline hydraulic oil filter series is a proven filter concept, with multiple connection options up to 500l/min and pressures up to 420 bar.

View Series Page

Share / Email

Print

Pr

Technical Specifications

Flow Rate:

Division: Hydraulic and Industrial Process Filtration EMEA

Brand: Parker Indicator Pressure 7.0 bar Setting:

Seal Material: Nitrile Technology: Filtration

Bypass Valve Pressure No by pass Rating:

Connection Type: G1½"

Mining

Material handling Construction Industry: Marine

Power Generation Industrial Machinery Injection Moulding

70/70 Eco Series

Options: For Fluid Type:

Application:

Operating Pressure: Operating Temperature:

Materials of

Drilling machines

Dumpers

Hydraulic power units Mobile cranes Reach stackers

Container handling equipment

Cranes Excavators Crushing machines Propulsion systems Deck machinery Wind turbines Hydropower Servo controls

No by pass Suitable for use with mineral and vegetable oils,

and some synthetic oils. 350 bar -40°C to +100°C

Head:

Cast iron (GSI). Construction:

Steel. Max torque 40 Nm.

A Safety Warning

Product Series:

Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.

Typical Applications

- Mobile working hydraulics
- · Mobile drive system
- · Injection moulding
- Servo controls
- · Die casting
- Machine tools

+ Follow Us:

· Industrial power units

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files + Related Documents + Parker Sales Company UK psc.uk.webform@support.parker.com +44 (0)1926 317878 + Company Information + Global Operations + Help & Support

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

SITE MAP SAFETY PRIVACY POLICIES TERMS AND CONDITIONS