

High Pressure In-Line Filter - 70/70 Eco Series

Part #: 70T110QBPKG166



High pressure inline hydraulic oil filter series is a proven filter concept, with multiple connection options up to 500l/min and pressures up to 420 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

| | | | |
|-------------------------------|---|----------------------------|--|
| Division: | Hydraulic and Industrial Process Filtration EMEA | | |
| Flow Rate: | 0 to 170 l/min | | |
| Brand: | Parker | | |
| Indicator Pressure Setting: | No indicator | | |
| Technology: | Filtration | Application: | Drilling machines Dumpers Hydraulic power units Mobile cranes Reach stackers Container handling equipment Cranes Excavators Crushing machines Propulsion systems Deck machinery Wind turbines Hydropower Servo controls |
| Seal Material: | Nitrile | Options: | Side indicator port |
| Product Series: | 70/70 Eco Series | For Fluid Type: | Suitable for use with mineral and vegetable oils, and some synthetic oils. |
| Bypass Valve Pressure Rating: | 3.5 bar | Operating Pressure: | 420 bar |
| | Mining Material handling Construction Marine Power Generation Industrial Machinery Injection Moulding | Operating Temperature: | -40°C to +100°C |
| Industry: | | Materials of Construction: | Head: Cast iron (GSI). |
| Connection Type: | G1" | | Bowl: Steel. Max torque 40 Nm. |

Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.

Typical Applications

- Mobile working hydraulics
- Mobile drive system
- Injection moulding
- Servo controls
- Die casting
- Machine tools
- Industrial power units

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

CAD Drawings + Files

Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :

© PARKER HANNIFIN CORP 2024

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) [SAFETY](#) [PRIVACY POLICIES](#) [TERMS AND CONDITIONS](#)

