

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [High Pressure In-...](#) / 70T210QHBPXG162

[Services](#)
High Pressure In-Line Filter - 70/70 Eco Series

[Solutions](#)

Part #: 70T210QHBPXG162

[Where to Buy](#)



High pressure inline hydraulic oil filter series is a proven filter concept, with multiple connection options up to 500l/min and pressures up to 420 bar.

[View Series Page](#) [Share / Email](#) [Print](#)

Technical Specifications

<p>Flow Rate: 0 to 280 l/min</p> <p>Division: Hydraulic and Industrial Process Filtration EMEA</p> <p>Brand: Parker</p> <p>Indicator Pressure Setting: No indicator</p> <p>Technology: Filtration</p> <p>Seal Material: Nitrile</p> <p>Bypass Valve Pressure Rating: No by pass</p> <p>Product Series: 70/70 Eco Series</p> <p>Connection Type: G1"</p>	<p>Application:</p> <p>For Fluid Type:</p> <p>Operating Pressure: 420 bar</p> <p>Operating Temperature: -40°C to +100°C</p> <p>Materials of Construction:</p>	<p>Drilling machines</p> <p>Dumpers</p> <p>Hydraulic power units</p> <p>Mobile cranes</p> <p>Reach stackers</p> <p>Container handling equipment</p> <p>Cranes</p> <p>Excavators</p> <p>Crushing machines</p> <p>Propulsion systems</p> <p>Deck machinery</p> <p>Wind turbines</p> <p>Hydropower</p> <p>Servo controls</p> <p>Suitable for use with mineral and vegetable oils, and some synthetic oils.</p> <p>Head: Cast iron (GSI).</p> <p>Bowl: Steel. Max torque 40 Nm.</p>
<p>Industry:</p> <p>Options:</p>	<p>Mining</p> <p>Material handling</p> <p>Construction</p> <p>Marine</p> <p>Power Generation</p> <p>Industrial Machinery</p> <p>Injection Moulding</p> <p>No by pass</p>	

Safety Warning

Item Information

The 70/70 Eco Series of high pressure filters are designed to satisfy demanding applications in the mobile and industrial markets. With multiple mounting options, this high pressure filter series is right filter for many applications. The 70/70 Eco Series filter series has a wide range of high capacity and low initial differential pressure elements, including a no metal content Eco element, offering excellent protection to system components.

The 70/70 Eco Serie offers several bowl lengths to secure the lowest possible pressure drop for each application. For critical applications such as servo or proportional controls, a no bypass high strength element combination ensures maximum protection.

The low hystereis differential pressure indicator fitted to this series is unrivalled in its performance.

For more information or a detailed discussion about your specific requirements please contact Parker or an authorised Parker distributor.

Industries

CAD Drawings + Files



Solutions

Related Documents



Where to Buy



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+441926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :



[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)
