

[Home](#)

[Products](#)

[Support](#)

[Industries](#) / [Products](#) / [Filters, Collecto...](#) / [Filter Assemblies...](#) / [Hydraulic Filters](#) / [Medium Pressure I...](#) / 80CN210QEBM2KY324

Medium Pressure Inline Filters CN Series

[Solutions](#)

Part #: 80CN210QEBM2KY324

[Where to Buy](#)



The CN Series is a compact, cost effective, medium pressure filter designed with coreless filtration technology. CN Series bowl features a permanently fixed core designed to reduce solid waste and minimize disposal costs with every element change out.

[View Series Page](#)

[View Catalog\(s\)](#)

[Share / Email](#)

[Print](#)

Technical Specifications

Mounting Style:	Inline	Micron Rating:	10 µm
Flow Rate:	130 gpm (492 lpm)	Indicator Type:	Visual automatic reset
Pressure Rating:	1000 psi (69 bar)	Housing Material:	Aluminum
Filter Element Type:	10Q Microglass	Indicator Pressure Setting:	50 psi (3.4 bar)
Seal Material:	Nitrile	For Fluid Type:	Mineral, Petroleum and Polyalphaolefin (PAO) based fluids
Port Connection Type:	Flange face, SAE 2", Code 6	Maximum Operating Temperature:	225 F (107 C)
Specifications Met:	n/a	Weight:	15.2 lbs (6.89 kg)
Bypass Valve Pressure Rating:	50 psi (3.4 bar)	Compatible Element:	936718Q
Options:	Drain port	Product Style:	Hydraulic Filter
Port Type:	Flange face, SAE 2", Code 6	Product Type:	Hydraulic Filter

[Safety Warning](#)

Item Information

- Compressor Lube Oil
- Off-line Filter Loops
- Machine Tools (Automotive Standard)
- Hydrostatic Drive Charge Pumps
- Mobile Equipment
- Pilot Lines for Servo Controls
- Oil Patch Drilling Equipment
- Injection Molding

This partial list of applications for Parker CN series filters has a common factor, the need for an economical, medium pressure range filter with excellent fatigue pressure ratings. Prior to the availability of the CN filter, applications such as those listed were restricted by limitations on can, or forced into the higher cost range of high pressure filters.





this gap, and now with the newly increased fatigue rating from 550 to 800 psi, the applications are expanded.

Features

- 800 psi fatigue rating (eight times that of a spin-on)
- Diametral (side) seal between head and bowl

Products

- Dust Seal
- Cast aluminum head

Support

- Standard Microglass elements
- Complete performance data disclosure

Industries

- Electrical or electrical/visual indicators available

Services

- Ability to provide reliable service under tough cyclic operating conditions

Solutions

- Solutions utilized in applications where high pressure filters may have been only option

Where to Buy

- Prevents contamination from building up on bowl / head threads

- Low profile, lightweight and durable
- Multi-layered design produced high capacity and efficiency
- Reduces pleat bunching, keeps performance consistent
- All pertinent information is provided in an easy-to-compare format
- Check element condition at a glance
- Right style for the application

Benefits

- Reduced downtime due to premature filter failures
- Reduced costs, better "fit" for the application
- No downtime, no leaks
- Performs with "real world" service
- Easier service, no galling
- Less weight, smaller envelop and cleaner appearance
- Great performance value
- Reliable performance throughout element life
- Reduces downtime, maximizes element life
- No hidden deficiencies
- Easy selection of proper filtration
- Optimize element life, prevent bypassing
- Matches your system electrical connections

CAD Drawings + Files



Related Documents



Parker Sales Company UK

psc.uk.webform@support.parker.com
[+44 \(0\)1926 317878](tel:+44(0)1926317878)

+ Company Information

+ Global Operations

+ Help & Support

+ Follow Us :





[Home](#)

[Products](#)

[Support](#)

[Industries](#)

[Services](#)

[Solutions](#)

[Where to Buy](#)

